



IQTouch TE1200U-1



Data Sheet

- **The advanced Android 12**

- Slidable home pages allow customizable access for more user-friendly experience.

- **Precision Touch and Writing Enhancement**

Advanced ZERO+ bonding technology, full-channel 40-point touch control, 20-point writing capabilities, and a minimum touch object size of just 2 mm.

- **Q Button Customization**

Offer one-click access to customized functions, streamlining your experience for quick access to your desired features.

- **Wireless Presentation system**

Wireless presentation for easy casting from mobile phone/laptop/tablet..



Display

Model	LE065MD	LE075MD	LE086MD
Diagonal Size	65"	75"	86"
Brightness	350cd/m ²		
Contrast Ratio	1200: 1		1600: 1
Panel Type	TFT		
Backlight	Direct LED (DLED)		
Resolution	4K UHD (3840*2160)		
Display Ratio	16:9		
Response Rate	8ms (typ.)		
Refreshing Frequency	60Hz		
Viewing Angle	178 ° (H), 178 ° (V)		
Backlight Life Time	50,000 hrs		
Display Colors	10bit(1.07B)		
Glass	4mm Tempered Glass with Anti-Glare coating (MOHS 7)		
Dynamic Contrast Ratio	5000: 1		
Touch Technology	Infrared		
Touch Point	40-point touch; 40-point writing under Windows; 20-point writing under Android;		
Touch Resolution	32768 x 32768		
Response Rate	<4ms(single touch) <6ms(max touch inputs)		
Touch Accuracy	≤1mm		
Recognition	Finger or pen		
Writing Height	3mm		
Minimum Touch Object	2mm		
Supported O.S.	HID Support & Win10/Win8/Win7/Mac OS /Android/Chrome OS/Linux		

Power

	65"	75"	86"
Voltage	100-240V, AC 50-60 Hz		
Maximum Power	≤350W	≤400W	≤450W
Standby Power	≤0.5W		

Physical Specifications

	65"	75"	86"
Net Weight	40Kg ± 1.5 Kg	56Kg ± 1.5 Kg	66Kg ± 1.5 Kg
Gross Weight	46Kg ± 1.5 Kg	70Kg ± 1.5Kg	81Kg ± 1.5Kg
Product Size (mm) (W*H*D)	1490* 906*89	1712* 1031*89	1959* 1170*89
Packing Size (mm) (W*H*D)	1576* 980*200	1800* 1125*200	2044* 1262*200
VESA Hole Position (mm)	4-M8 screw hole 500*400	4-M8 screw hole 600*400	4-M8 screw hole 800*400

Environmental

Working Temperature	0°C ~ 40°C
Storage Temperature	-20°C ~ 60°C
Working Humidity	20% ~ 80% RH Non-Condensing
Storage Humidity	20% ~ 90% RH Non-Condensing



Front Buttons

Front Buttons	POWER
---------------	-------

Connectivity

Front	USB3.0 (Android&PC)	1
	HDMI IN 2.0	1
	Touch-USB	1
	USB-C	1
	USB2.0	1

Input	RJ45 (10/100MB)	1
	HDMI 2.0 (4K@60fps)	1
	USB 2.0 (Android)	1
	USB 3.0 (Android&PC)	1
	USB 2.0 (for Touch)	1
	TF Card	1
	RS232	1

Output	COAX SPDIF OUT	1
	EARPHONE	1

--	--	--

Speakers	15W * 2
----------	---------

Light Sensor	YES
--------------	-----

Temperature Monitor	YES
---------------------	-----

Language

OSD	English, French, German, Russian, Japanese, Korean, Polish, Portuguese, Vietnamese, Albania Spanish, Italian, Arabic, Simplified Chinese, Traditional Chinese
-----	---

Android

CPU Framework	A55*8
---------------	-------

CPU Processor Speed	1.2Ghz
---------------------	--------

GPU	Quad-core MaliG52 600MHz
-----	--------------------------

RAM	4G
-----	----

ROM	32G
-----	-----

OS Version	Android 12.0
------------	--------------

--	--

WiFi & Hotspot	IEEE 802.11 a/b/g/n/ac, IEEE 802.1x, WPA2, and station mode(2.4G/5G Dual-band);
----------------	---

Bluetooth	5.0
-----------	-----

OPS (Optional)

Chipset	Intel
---------	-------

CPU	Intel®Core i3/i5/i7
-----	---------------------

Memory	4GB/8GB/16GB
--------	--------------

HDD	500GB/1TB
-----	-----------

SSD(optional)	128GB/256GB/512GB
---------------	-------------------

